



Weld Current Meter

- The WA1 weld analyser offers the engineering professional the facilities to analyse, fault find, and improve the process quality on today's sophisticated welding control systems.
- Full NAMAS traceability gives you the confidence in your processes that your customers demand.
- Includes 150mm flexible toroid, 3 x AA batteries, charger and carry case
- Measures 0—60 kA , 9999 cycles AC, 199 seconds DC, no of pulses, conduction angle, weld time.
- Fitted with RS232 communications port.



Weld Gauge

Part No	Pressure Lbs	Pressure Kgs	Pressure N
Presstotest A	0-600	0-275	0-2750
Presstotest B	0-1000	0-450	0-4500
Presstotest C	0-2000	0-900	0-9000
Presstotest D	0-4000	0-1800	0-18000



Cap Removal Tools

Part No	Description
CRT 1	Cam Type 10mm-22mm
PRO-M00483	Jaw Type With Hammer 10mm-16mm
CRT8HD	Jaw Type 16mm-20mm
CRT6HD	Jaw Type 10mm-16mm



Tapered Reamers

Part No	Description
1/2 Reamer	1/2" BS807 5 Degree Inc Reamer
5/8 Reamer	5/8" BS807 5 Degree Inc Reamer
3/4 Reamer	3/4" BS807 5 Degree Inc Reamer



Torque Testing Sockets For Square Nuts

Part No	A/F mm	Drive A/F mm
M4	7	3/8"
M5	9	3/8"
M6	10	3/8"
M8	14	1/2"
M10	17	1/2"
M12 & 7/16	19	1/2"



The INSULATION BAND is used where permanent insulation of the part is required.

Fibreglass band coated in epoxy resin guarantees a permanent insulation up to 11,000 volts and is heat resistant up to 300 deg C.

50mm wide x 1500mm long



Jointing And Sealing Compounds

HERMATITE RED - Semi hardening gasket compound.

COPPER GREASE - Conductive grease.